



# Slangefittings

DIN	<b>CA</b>  DKOL Female Metric 24" Light Series with O-ring Swivel - Straight	<b>CE</b>  DKOL 45° Female Metric 24" Light Series with O-ring Swivel - 45° Elbow	<b>CF</b>  DKOL 90° Female Metric 24" Light Series with O-ring Swivel - 90° Elbow	<b>DO</b>  Male Metric 24" Light Series - Rigid Straight (Ball Nose)	<b>CO</b>  Female Metric Series LL Swivel (Ball Nose) Straight	<b>C3</b>  DKL Female Metric Light Series - Swivel Straight (Ball Nose)	<b>C4</b>  DKL 45° Female Metric Light Series - Swivel 45° Elbow (Ball Nose)	<b>C5</b>  DKL 90° Female Metric Light Series - Swivel 90° Elbow (Ball Nose)	<b>1D</b>  BEL Metric Standpipe Light Series - Rigid Straight	<b>DD</b>  BEL 45° Metric Standpipe Light Series - Rigid 45° Elbow	<b>5D</b>  BEL 90° Metric Standpipe Light Series - Rigid 90° Elbow	<b>C9</b>  DKOS Female Metric 24" Heavy Series with O-ring Swivel - Straight
	<b>OC</b>  DKOS 45° Female Metric 24" Heavy Series with O-ring Swivel - 45° Elbow	<b>1C</b>  DKOS 90° Female Metric 24" Heavy Series with O-ring Swivel - 90° Elbow	<b>D2</b>  CES Male Metric 24" Heavy Series Rigid - Straight	<b>C6</b>  DKS Female Metric Heavy Series - Swivel Rigid (Ball Nose)	<b>3D</b>  BES Metric Standpipe Heavy Series Rigid - Straight	<b>49</b>  Metric Banjo - Straight	<b>9B</b>  Metric - Light Series Swivel Female 45° Elbow	<b>9C</b>  Light Series Metric Swivel Female 90° Elbow				
BSP	<b>92</b>  DKR Female BSP Parallel Pipe - Swivel - Straight (60° Cone)	<b>B1</b>  DKR 45° Female BSP Parallel Pipe Swivel - 45° Elbow (60° Cone)	<b>B2</b>  DKR 90° Female BSP Parallel Pipe Swivel - 90° Elbow (60° Cone)	<b>B4</b>  DKR 90° Female BSP Parallel Pipe - Swivel 90° Elbow Block Type (60° Cone)	<b>EA</b>  DKOR BSP Swivel Female with O-ring (60° Cone)	<b>EB</b>  DKOR 45° BSP Swivel Female with O-ring - 45° Elbow (60° Cone)	<b>EC</b>  DKOR 90° BSP Swivel Female with O-ring - 90° Elbow (60° Cone)	<b>D9</b>  AGR Male BSP Parallel Pipe Rigid - Straight (60° Cone)	<b>91</b>  AGR-K Male BSP Taper Pipe Rigid - Straight	<b>B5</b>  Female BSP Parallel Pipe Swivel - Straight (Flat Seat)	<b>34</b>  Inch Standpipe (Brass)	
	<b>O1</b>  AGN Male NPTF Pipe Rigid - Straight	<b>O2</b>  Female NPTF Pipe Rigid - Straight	<b>O3</b>  AGJ Male JIC 37" Rigid - Straight	<b>O4</b>  Male SAE 45° Rigid - Straight	<b>O5</b>  Male SAE Straight Thread with O-Ring - Rigid Straight	<b>O6 68</b>  DKJ Female - JIC 37" / SAE 45° Dual Flare Swivel - Straight	<b>O8</b>  Female SAE 45° Swivel - Straight	<b>13</b>  Male NPTF Pipe Swivel	<b>33</b>  Male JIC 37" - Rigid 45° Elbow	<b>37 3V</b>  DKJ 45° Female JIC 37" / SAE 45° Dual Flare - Swivel Female - 45° Elbow	<b>39 3W</b>  DKJ 90° Male JIC 37" / SAE 45° Dual Flare - Swivel Female - 90° Elbow	<b>41 3Y</b>  DKJ 90° L Female JIC 37" / SAE 45° Dual Flare - Swivel Female - 90° Elbow long
SAE	<b>L9</b>  DKJ 90° M Female JIC 37" Swivel - 90° Elbow Medium Drop	<b>93</b>  Female JIC 37" - Swivel (Block Type)										
	<b>15 4A</b>  SFL SAE Code 61 Straight (5000 psi)	<b>16</b>  SFL 22.5° / 3000 psi SAE Code 61 22.5° Elbow	<b>17 4F</b>  SFL 45° / 3000 psi SAE Code 61 45° Elbow	<b>19 4N</b>  SFL 90° SAE Code 61 90° Elbow (5000 psi)	<b>6A</b>  SFS / 6000 psi SAE Code 62 Straight	<b>6F</b>  SFS 45° / 6000 psi SAE Code 62 45° Elbow	<b>6N</b>  SFS 90° / 6000 psi SAE Code 62 90° Elbow	<b>89</b>  SAE Code 61 90° Elbow (Long) Standard Series	<b>XA</b>  Caterpillar <sup>®</sup> Flange Head - Straight	<b>XF</b>  Caterpillar <sup>®</sup> Flange Head 45° Elbow	<b>XG</b>  Caterpillar <sup>®</sup> Flange Head 60° Elbow	<b>XN</b>  Caterpillar <sup>®</sup> Flange Head 90° Elbow
Flange	<b>JC</b>  Female ORFS - Swivel Straight - Short	<b>JS</b>  ORFS Swivel Female (Long)	<b>J7</b>  Female ORFS - Swivel 45° Elbow	<b>J9</b>  Female ORFS - Swivel 90° Elbow - Short Drop	<b>J1</b>  Female ORFS - Swivel 90° Elbow - Long Drop	<b>J5</b>  Female ORFS - Swivel 90° Elbow - Medium Drop	<b>JM</b>  ORFS Male	<b>JD</b>  Male ORFS - Bulkhead with Locknut (with O-Ring)				
	<b>FU</b>  GUI Female BSP Parallel Pipe - Swivel - Straight (30° Flare)	<b>GU</b>  GUO Female BSP Parallel Pipe - Swivel - Straight (60° Cone)	<b>MU</b>  Female Metric Swivel Straight (30° Flare)	<b>MZ</b>  Female Metric Swivel - 90° Elbow (30° Flare)	<b>UT</b>  Male BSP Taper Pipe Rigid - Straight (60° Cone)							
JIS	<b>FG</b>  Male French Gas Series Rigid - Straight (24° Cone)	<b>F2</b>  Female French Swivel Female Gas Series - 90° Elbow	<b>F4</b>  Female French Gas Series - Swivel Straight (Ball Nose)	<b>F6</b>  French Male Metric Series (24° Cone)	<b>F9</b>  French Swivel Female Metric Series (Ball Nose)	<b>FA</b>  Metric Male for Agriculture Valves						
	<b>CW</b>  Power Cleaner Connection	<b>PW</b>  Male Kärcher Metric Cleaning Hose Fitting Rigid - Straight	<b>NW</b>  Female Kärcher Metric Cleaning Hose Fitting Swivel - Straight (New Design)									
Fransk Standard	<b>FG</b>  Male French Gas Series Rigid - Straight (24° Cone)	<b>F2</b>  Female French Swivel Female Gas Series - 90° Elbow	<b>F4</b>  Female French Gas Series - Swivel Straight (Ball Nose)	<b>F6</b>  French Male Metric Series (24° Cone)	<b>F9</b>  French Swivel Female Metric Series (Ball Nose)	<b>FA</b>  Metric Male for Agriculture Valves						
	<b>CW</b>  Power Cleaner Connection	<b>PW</b>  Male Kärcher Metric Cleaning Hose Fitting Rigid - Straight	<b>NW</b>  Female Kärcher Metric Cleaning Hose Fitting Swivel - Straight (New Design)									
Højtryksrensning	<b>CW</b>  Power Cleaner Connection	<b>PW</b>  Male Kärcher Metric Cleaning Hose Fitting Rigid - Straight	<b>NW</b>  Female Kärcher Metric Cleaning Hose Fitting Swivel - Straight (New Design)									
	<b>XU</b>  Female Metric Swivel - Straight (30° Flare)	<b>XY</b>  Female Metric Swivel - 90° Elbow (30° Flare)	<b>DK</b>  Male Metric L - Rigid Bulkhead with Locknut (24° Cone)	<b>DX</b>  Female Metric Swivel (M27x2) O-Ring - Light Series	<b>FF</b>  Metru-Lok Swivel Female	<b>AF</b>  Male BSP Parallel Pipe Rigid - Straight (with O-Ring Seal)	<b>NM</b>  Male BSP Parallel Pipe - L Series - Rigid Straight - ED-Seal	<b>YW</b>  Male Standpipe - Rigid Straight - A-Lok	<b>VW121</b>  BSP Swivel Female	<b>82</b>  Push-Lok <sup>®</sup> Union	<b>DP</b>  Metric Swivel Female Tee / Male Stud	<b>DR</b>  Metric Swivel Female Tee
Andre	<b>5C</b>  60° Cone Swivel Female	<b>6C</b>  60° Cone Swivel Female 45° Elbow	<b>7C</b>  60° Cone Swivel Female 90° Elbow	<b>5S</b>  Female Tube O-Ring Swivel - Short Pilot	<b>5H</b>  Female Tube O-Ring Swivel - 45° Elbow Short Pilot	<b>5T</b>  Female Tube O-Ring Swivel - Long Pilot Charge Port at 180° for R134a	<b>59PT</b>  Male Tube O-Ring Swivel - Long Pilot Charge Port at 180° for R134a	<b>5LPT</b>  Female Tube O-Ring Swivel - Long Pilot Charge Port at 180° for R134a	<b>T1</b>  Male Refrigerant Tube Mender - Straight (with Nut and Ferrule)			
	<b>5C</b>  60° Cone Swivel Female	<b>6C</b>  60° Cone Swivel Female 45° Elbow	<b>7C</b>  60° Cone Swivel Female 90° Elbow	<b>5S</b>  Female Tube O-Ring Swivel - Short Pilot	<b>5H</b>  Female Tube O-Ring Swivel - 45° Elbow Short Pilot	<b>5T</b>  Female Tube O-Ring Swivel - Long Pilot Charge Port at 180° for R134a	<b>59PT</b>  Male Tube O-Ring Swivel - Long Pilot Charge Port at 180° for R134a	<b>5LPT</b>  Female Tube O-Ring Swivel - Long Pilot Charge Port at 180° for R134a	<b>T1</b>  Male Refrigerant Tube Mender - Straight (with Nut and Ferrule)			

Parker varenr opbygning



## ToughShield™ Plus

Parkers zink-nikkel overfladebehandling, ToughShield Plus, er den første kommercielt tilgængelige belægning, der giver op til 3.000 timers beskyttelse mod rød rust korrosion. Testet i henhold til ASTM B117 neutral saltspraytest.



Se mere på [hymatik.com](http://hymatik.com)