
PTR44M* Thread reducer

Male BSPP thread O-ring + retaining ring (ISO 1179) / Female BSPP thread (ISO 1179-1)
*To Be Phased out, Replaced by RI-ED Range ** See chapter I



Thread BSPP T1	Thread BSPP T2	C mm	L1 mm	L2 mm	Weight (steel) g/1 piece	Adapter Steel	Equivalent type Replacement (WITH ED SEAL**)	Adapter Stainless Steel	Equivalent type Replacement (WITH ED SEAL**)	PN (bar)
1/4	1/8	19	11.0	29	35	**1/4X1/8PTR44MS**	**RI1/4EDX1/8A3C**	**1/4X1/8PTR44MSS**	**RI1/4EDX1/871**	400
3/8	1/4	22	11.0	36	58	**3/8X1/4PTR44MS**	**RI3/8EDX1/4A3C**	**3/8X1/4PTR44MSS**	**RI3/8EDX1/471**	400
1/2	1/4	30	14.5	24	98	**1/2X1/4PTR44MS**	**RI1/2EDX1/4A3C**	**1/2X1/4PTR44MSS**	**RI1/2EDX1/471**	400
1/2	3/8	30	14.5	37	118	**1/2X3/8PTR44MS**	**RI1/2EDX3/8A3C**	**1/2X3/8PTR44MSS**	**RI1/2EDX3/871**	400
3/4	1/4	36	14.5	26	163	**3/4X1/4PTR44MS**	**RI3/4EDX1/4A3C**	**3/4X1/4PTR44MSS**	**RI3/4EDX1/471**	400
3/4	3/8	36	14.5	26	118	**3/4X3/8PTR44MS**	**RI3/4EDX3/8A3C**	**3/4X3/8PTR44MSS**	**RI3/4EDX3/871**	315
3/4	1/2	36	14.5	43	146	**3/4X1/2PTR44MS**	**RI3/4EDX1/2A3C**	**3/4X1/2PTR44MSS**	**RI3/4EDX1/271**	315
1	1/4	46	18.5	29	245	**1X1/4PTR44MS**	**RI1EDX1/4A3C**	**1X1/4PTR44MSS**	**RI1EDX1/471**	315
1	3/8	46	18.5	29	260	**1X3/8PTR44MS**	**RI1EDX3/8A3C**	**1X3/8PTR44MSS**	**RI1EDX3/871**	315
1	1/2	46	18.5	29	273	**1X1/2PTR44MS**	**RI1EDX1/2A3C**	**1X1/2PTR44MSS**	**RI1EDX1/271**	315
1	3/4	46	18.5	49	240	**1X3/4PTR44MS**	**RI1EDX3/4A3C**	**1X3/4PTR44MSS**	**RI1EDX3/471**	315

Parker Adapter are delivered with NBR elastomeric seals as standard. For more details on other seal materials see page N61.
Order codes shown are part of our current manufacturing programme.
Imperial and metric parts may vary in hexagon dimensions.

$\frac{\text{PN (bar)}}{10} = \text{PN (MPa)}$

Pressure ratings – PN shown, apply to the Steel and Stainless Steel versions of the product.

N

Tel: +45 63 12 83 00 | Email: ps@hymatik.com | www.hymatik.com | Hvidkaervej 27a, DK-5250 Odense SV, Denmark