

# Tube to O-Ring Seal

## Tube End to O-Ring Straight Thread

***For fractional tube***






| CPI™ PART NO. | A-LOK® PART NO. | INTER-CHANGES WITH | INCHES | | | | | | | O-RING ARP UNIFORM DASH NO. |
|---|---|---|---|---|---|---|---|---|---|---|
| | | | T TUBE O.D. | SAE STRAIGHT THREAD | A | K | R | X DIA. | W HEX | |
| 2-2 T2HOA5 | 2M2TU2 | 2-TA-OR-ST | 1/8 | 5/16-24 | 1.22 | 0.53 | .34 | 0.55 | 9/16 | 2-011 |
| 3-3 T2HOA5 | 3M2TU3 | 3-TA-OR-ST | 3/16 | 3/8-24 | 1.38 | 0.56 | .38 | 0.62 | 5/8 | 2-012 |
| 4-4 T2HOA5 | 4M2TU4 | 4-TA-OR-ST | 1/4 | 7/16-20 | 1.55 | 0.63 | .41 | 0.74 | 3/4 | 2-111 |
| 5-5 T2HOA5 | 5M2TU5 | 5-TA-OR-ST | 5/16 | 1/2-20 | 1.64 | 0.66 | .44 | 0.86 | 7/8 | 2-112 |
| 6-6 T2HOA5 | 6M2TU6 | 6-TA-OR-ST | 3/8 | 9/16-18 | 1.70 | 0.69 | .47 | 0.93 | 15/16 | 2-113 |
| 8-8 T2HOA5 | 8M2TU8 | 8-TA-OR-ST | 1/2 | 3/4-16 | 1.95 | 0.91 | .47 | 1.12 | 1-1/8 | 2-116 |
| 10-10 T2HOA5 | 10M2TU10 | 10-TA-OR-ST | 5/8 | 7/8-14 | 2.12 | 0.97 | .47 | 1.30 | 1-3/8 | 2-212 |
| 12-12 T2HOA5 | 12M2TU12 | 12-TA-OR-ST | 3/4 | 1-1/16-12 | 2.16 | 0.97 | .56 | 1.49 | 1-1/2 | 2-215 |
| 16-16 T2HOA5 | 16M2TU16 | 16-TA-OR-ST | 1 | 1-5/16-12 | 2.47 | 1.22 | .56 | 1.74 | 1-3/4 | 2-219 |

**NOTE:** Add -Z6 for assembly of nuts and ferrules on the tube stub end. Dimensions for reference only, subject to change.

Parts are supplied with nitrile o-rings as standard. For Fluorocarbon o-rings, add the suffix "-VO". Other o-rings available upon request.



Tel: +45 63 12 83 00 | Email: ps@hymatik.com | www.hymatik.com | Hvidkaervej 27a, DK-5250 Odense SV, Denmark