
## F4OHG5 Male female thread adapter

Male BSPP thread O-ring + retaining ring (ISO 1179) /
Female UN/UNF thread – O-ring (ISO 11926-1)




| Thread BSPP T4 | Thread UN/UNF-2B T5 | C1 mm | D mm | L mm | LL mm | Weight (steel) g/1 piece | Adapter Steel | Adapter Stainless Steel | PN (bar) S | PN (bar) SS |
|---|---|---|---|---|---|---|---|---|---|---|
| 1/8-28 | 7/16-20 | 17.5 | 4.4 | 25 | 19 | 27 | **1/8-4F4OHG5S** | **1/8-4F4OHMG5SS** | 350 | 315 |
| 1/4-19 | 7/16-20 | 19 | 7.5 | 28 | 17 | 40 | **1/4-4F4OHG5S** | **1/4-4F4OHMG5SS** | 350 | 315 |
| 1/4-19 | 9/16-18 | 20.6 | 7.5 | 32 | 22 | 45 | **1/4-6F4OHG5S** | **1/4-6F4OHMG5SS** | 350 | 315 |
| 3/8-19 | 9/16-18 | 22.2 | 9.9 | 32 | 22 | 70 | **3/8-6F4OHG5S** | **3/8-6F4OHMG5SS** | 350 | 315 |
| 3/8-19 | 3/4-16 | 25.4 | 9.9 | 34 | 24 | 73 | **3/8-8F4OHG5S** | **3/8-8F4OHMG5SS** | 350 | 280 |
| 1/2-14 | 7/8-14 | 28.6 | 12.3 | 41 | 28 | 111 | **1/2-10F4OHG5S** | **1/2-10F4OHMG5SS** | 240 | 240 |
| 3/4-14 | 1 1/16-12 | 35 | 15.5 | 44 | 32 | 177 | **3/4-12F4OHG5S** | **3/4-12F4OHMG5SS** | 240 | 240 |
| 1-11 | 1 5/16-12 | 44.5 | 21.4 | 49 | 33 | 272 | **1-16F4OHG5S** | **1-16F4OHMG5SS** | 240 | 210 |
| 1 1/4-11 | 1 5/8-12 | 50.8 | 27.4 | 50 | 33 | 320 | **1 1/4-20F4OHG5S** | **11/4-20F4OHMG5SS** | 140 | 140 |

Parker Adapter are delivered with NBR elastomeric seals as standard. For more details on other seal materials see page O60.

Order codes shown are part of our current manufacturing programme.

Imperial and metric parts may vary in hexagon dimensions.

$\frac{\text{PN (bar)}}{10} = \text{PN (MPa)}$

Do not create drawings from these dimensions, they are subject to change and ISO manufacturing allowances.



Tel: +45 63 12 83 00 | Email: ps@hymatik.com | www.hymatik.com | Hvidkaervej 27a, DK-5250 Odense SV, Denmark