
## F682EDMX Swivel male stud

Triple-Lok® 37° Flare female swivel end / Male metric thread – ED seal (ISO 9974)




| Tube O.D. mm | Tube O.D. in. | Thread Metric T82 | Thread UN/UNF-2B T6 | C4 mm | C3 mm | D mm | D2 mm | L5 mm | LL mm | Weight (steel) g/1 piece | Triple-Lok® Steel | Triple-Lok® Stainless Steel | PN (bar) S | PN (bar) SS |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 6 | 1/4 | M 10×1.0 | 7/16-20 | 14 | 14 | 4.4 | 4 | 32 | 15 | 28 | **4M10F682EDMXS** | **4M10F682EDMXSS** | 500 | 350 |
| 8 | 5/16 | M 12×1.5 | 1/2-20 | 17 | 17 | 6 | 6 | 38 | 17 | 32 | **5M12F682EDMXS** | **5M12F682EDMXSS** | 420 | 350 |
| 10 | 3/8 | M 14×1.5 | 9/16-18 | 19 | 19 | 7.5 | 7 | 40 | 18 | 42 | **6M14F682EDMXS** | **6M14F682EDMXSS** | 350 | 350 |
| 12 | 1/2 | M 16×1.5 | 3/4-16 | 22 | 22 | 9.9 | 9 | 44 | 21 | 62 | **8M16F682EDMXS** | **8M16F682EDMXSS** | 350 | 350 |
| 12 | 1/2 | M 18×1.5 | 3/4-16 | 24 | 22 | 9.9 | 11 | 44 | 21 | 70 | **8M18F682EDMXS** | **8M18F682EDMXSS** | 350 | 350 |
| 14, 15, 16 | 5/8 | M 18×1.5 | 7/8-14 | 24 | 27 | 12.3 | 11 | 48 | 23 | 125 | **10M18F682EDMXS** | **10M18F682EDMXSS** | 350 | 350 |
| 14, 15, 16 | 5/8 | M 22×1.5 | 7/8-14 | 27 | 27 | 12.3 | 14 | 50 | 23 | 155 | **10M22F682EDMXS** | **10M22F682EDMXSS** | 350 | 350 |
| 18, 20 | 3/4 | M 22×1.5 | 1 1/16-12 | 27 | 32 | 15.5 | 14 | 52 | 24.5 | 160 | **12M22F682EDMXS** | **12M22F682EDMXSS** | 350 | 350 |
| 18, 20 | 3/4 | M 27×2.0 | 1 1/16-12 | 32 | 32 | 15.5 | 15.5 | 55 | 24.5 | 172 | **12M27F682EDMXS** | **12M27F682EDMXSS** | 350 | 350 |
| 25 | 1 | M 33×2.0 | 1 5/16-12 | 41 | 38 | 21.5 | 23 | 61 | 26.5 | 259 | **16M33F682EDMXS** | **16M33F682EDMXSS** | 250 | 250 |
| 28, 30, 32 | 1 1/4 | M 42×2.0 | 1 5/8-12 | 50 | 50 | 27.5 | 30 | 68 | 32 | 484 | **20M42F682EDMXS** | **20M42F682EDMXSS** | 250 | 210 |

Steel, stainless steel and brass Triple-Lok® parts are delivered with NBR elastomeric seals as standard. For more details on other seal materials see page K92.

Order codes shown are part of our current manufacturing programme.

Imperial and metric parts may vary in hexagon dimensions.

$\frac{\text{PN (bar)}}{10}$ = PN (MPa)

Do not create drawings from these dimensions, they are subject to change and ISO manufacturing allowances.

K



Tel: +45 63 12 83 00 | Email: ps@hymatik.com | www.hymatik.com | Hvidkaervej 27a, DK-5250 Odense SV, Denmark