
## HMX6 Swivel nut union

Triple-Lok® 37° Flare female swivel ends




| Tube O.D. mm | Tube O.D. in. | Thread UN/UNF-2B T6 | C3 mm | C4 mm | D mm | L mm | LL mm | Weight (steel) g/1 piece | Triple-Lok® Steel | Triple-Lok® Stainless Steel | PN (bar) S | PN (bar) SS |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 6 | 1/4 | 7/16-20 | 14.3 | 14.3 | 4.4 | 38 | 20 | 27 | **4 HX6-S** | **4HMX6SS** | 500 | 500 |
| 8, 10 | 5/16, 3/8 | 9/16-18 | 17.5 | 17.5 | 7.5 | 45 | 26 | 35 | **6 HX6-S** | **6HMX6SS** | 350 | 350 |
| 12 | 1/2 | 3/4-16 | 22.2 | 22.2 | 9.9 | 51 | 29 | 64 | **8 HX6-S** | **8HMX6SS** | 350 | 350 |
| 14, 15,16 | 5/8 | 7/8-14 | 25.4 | 25.4 | 12.3 | 58 | 32 | 115 | **10 HX6-S** | **10HMX6SS** | 350 | 350 |
| 18, 20 | 3/4 | 1 1/16-12 | 31.8 | 31.8 | 15.5 | 62 | 33 | 185 | **12 HX6-S** | **12HMX6SS** | 350 | 350 |
| 25 | 1 | 1 5/16-12 | 38 | 38 | 21.4 | 68 | 38 | 235 | **16 HX6-S** | **16HMX6SS** | 250 | 250 |

Order codes shown are part of our current manufacturing programme.

Imperial and metric parts may vary in hexagon dimensions.

$\frac{\text{PN (bar)}}{10}$ = PN (MPa)

Do not create drawings from these dimensions, they are subject to change and ISO manufacturing allowances.



Tel: +45 63 12 83 00 | Email: ps@hymatik.com | www.hymatik.com | Hvidkaervej 27a, DK-5250 Odense SV, Denmark