
C3T4 Male elbow

JIS BSPP 60° cone adapters (JIS B8363) / Male BSPT thread (ISO 7)




Thread BSPP T4	Thread BSPT T3	D mm	D2 mm	L1 mm	L2 mm	Y mm	Weight (steel) g/1 piece	Adapter Steel	PN (bar)
1/4-19	1/4-19	4.5	4.5	25	25	14	41	**4C3T4S**	315
3/8-19	3/8-19	7	7	30	29	19	74	**6C3T4S**	315
1/2-14	1/2-14	11	11	36	34	22	131	**8C3T4S**	200
3/4-14	3/4-14	15.9	15.9	43	38	27	146	**12C3T4S**	160
1-11	1-11	21	21	50	44	33.3	398	**16C3T4S**	120

Do not create drawings from these dimensions, they are subject to change and ISO manufacturing allowances.

V3T4 Male 45° elbow

JIS BSPP 30° Flare end (JIS B8363) / Male BSPT thread (ISO 7)



Thread BSPP T4	Thread BSPT T3	D mm	D2 mm	L4 mm	L5 mm	Y mm	Weight (steel) g/1 piece	Adapter Steel	PN (bar)
1/4-19	1/4-19	4.5	4.5	19	22	14	33	**4V3T4S**	315
3/8-19	3/8-19	7	7	22	25	19	64	**6V3T4S**	315
1/2-14	1/2-14	11	11	27	28	22	112	**8V3T4S**	200
3/4-14	3/4-14	15.9	15.9	30	32	27	162	**12V3T4S**	160
1-11	1-11	21	21	35	32	33.3	256	**16V3T4S**	120

Order codes shown are part of our current manufacturing programme.
Imperial and metric parts may vary in hexagon dimensions.

$\frac{\text{PN (bar)}}{10}$ = PN (MPa)

Do not create drawings from these dimensions, they are subject to change and ISO manufacturing allowances.

Tel: +45 63 12 83 00 | Email: ps@hymatik.com | www.hymatik.com | Hvidkaervej 27a, DK-5250 Odense SV, Denmark