

# 1C Female Metric 24° – Swivel Heavy Series with O-Ring 90° Elbow

ISO 12151-2-SWE-S – DKOS 90°



| Part Number | Hose I.D. | | | | Thread | A | B | E | W |
|---|---|---|---|---|---|---|---|---|---|
| | DN | Inch | Size | mm | metric | mm | mm | mm | mm |
| 11C77-16-8 | 12 | 1/2 | -8 | 12.7 | M24x1.5 | 77 | 42 | 45 | 30 |
| 11C77-16-10 | 16 | 5/8 | -10 | 15.9 | M24x1.5 | 92 | 53 | 45 | 30 |
| 11C77-20-10 | 16 | 5/8 | -10 | 15.9 | M30x2 | 92 | 53 | 53 | 36 |
| 11C77-20-10-STB60 | 16 | 5/8 | -10 | 15.9 | M30x2 | 115 | 76 | 37 | 36 |
| 11C77-20-12 | 19 | 3/4 | -12 | 19.1 | M30x2 | 108 | 62 | 60 | 36 |
| 11C77-20-12-STB60 | 19 | 3/4 | -12 | 19.1 | M30x2 | 134 | 88 | 41 | 36 |
| 11C77-25-12 | 19 | 3/4 | -12 | 19.1 | M36x2 | 108 | 62 | 58.5 | 46 |
| 11C77-25-12-STB60 | 19 | 3/4 | -12 | 19.1 | M36x2 | 133 | 87 | 40 | 46 |
| 11C77-25-12-SW41 | 19 | 3/4 | -12 | 19.1 | M36x2 | 108 | 62 | 59 | 41 |
| 11C77-30-12 | 19 | 3/4 | -12 | 19.1 | M42x2 | 108 | 62 | 61 | 50 |
| 11C77-25-16 | 25 | 1 | -16 | 25.4 | M36x2 | 131 | 77 | 69 | 46 |
| 11C77-30-16 | 25 | 1 | -16 | 25.4 | M42x2 | 131 | 77 | 69 | 50 |
| 11C77-30-16-SL120 | 25 | 1 | -16 | 25.4 | M42x2 | 131 | 77 | 120 | 50 |
| 11C77-30-20 | 31 | 1 1/4 | -20 | 31.8 | M42x2 | 145 | 82 | 73 | 50 |
| 11C77-38-20 | 31 | 1 1/4 | -20 | 31.8 | M52x2 | 151 | 87 | 78 | 60 |
| 11C77-38-24 | 38 | 1 1/2 | -24 | 38.1 | M52x2 | 179 | 112 | 101 | 60 |

Fittings with standard O-ring seals can be used for temperatures from -40 °C up to +105 °C.
O-rings see section Eb. Special O-rings are available on request.

Approved **fitting series** for **hose types**, depending on size:

77 | 387 | 387ST | 387TC | 487 | 487ST | 487TC | 787 | 787TC | 787ST | 797 | 797TC | 797ST | 797RH | SX42



Tel: +45 63 12 83 00 | Email: ps@hymatik.com | www.hymatik.com | Hvidkaervej 27a, DK-5250 Odense SV, Denmark