Nominal Diameter

8,5 = 60 mm²

Rectus Series

30



Steel coupling 3/8" according to ISO 6150 B and US MIL-SPEC 4109. Very robust design with steel valve bodies. The high insertion depth is guaranteed by an optimised plug guide.

Series 30 in brass material with nickel plating and with additional end connections available on request.

Working Temperature*
-20°C up to +100°C (NBR)
depending on the medium.

* For temperatures below -20°C and over +100°C and depending on the medium, other seal variants (FKM, EPDM, FFKM) are available.

KA Single Shut-Off

Working Pressure**

35 bar
** maximum static working pressure with design factor 4 to 1.

Material

Coupling: Brass / Steel
Plug: Steel nickel plated
Seals: NBR

Technical Description

Connecting Force 0 bar: 50 N
Connecting Force 6 bar: 110 N


Vacuum Coupling: 96%
Vacuum connected: 96%

Interchangeability (KA only)

- Industrial. Interchange 3/8"
- US-MIL-SPEC-C-4109
- ISO 6150 B
- Gromelle 900
- Hansen 4000
- Parker 30 3/8"




Flow diagrams

Air






Tel: +45 63 12 83 00 | Email: ps@hymatik.com | www.hymatik.com | Hvidkaervej 27a, DK-5250 Odense SV, Denmark

Couplings – with valve — Series 30KA

	Connection A	HEX mm	L mm	L1 mm	D mm	Part Number
 Male Thread	G 1/4	22	49	9	30	30KAAW13SPX
	G 3/8	22	49	9	30	30KAAW17SPX
	G 1/2	22	52	12	30	30KAAW21SPX
 Female Thread	G 1/4	22	49	11	30	30KAIW13SPX
	G 3/8	22	49	9	30	30KAIW17SPX
	G 1/2	22	52	12	30	30KAIW21SPX
 Hose Barb	6 mm	21	66	25	30	30KATF06SPX
	8 mm	21	66	25	30	30KATF08SPX
	10 mm	21	66	25	30	30KATF10SPX
	13 mm	21	66	25	30	30KATF13SPX

Plugs – without valve — Series 30KA

	Connection A	HEX mm	L mm	L1 mm	D mm	Part Number
 Male Thread	G 1/4	17	42	9		30SFAW13SXN
	G 3/8	19	42	9		30SFAW17SXN
	G 1/2	24	46	12		30SFAW21SXN
 Female Thread	G 1/4	17	40	10		30SFIW13SXN
	G 3/8	19	42	10		30SFIW17SXN
	G 1/2	24	43	12		30SFIW21SXN
 Hose Barb	8 mm		55	25	16	30SFTF08SXN
	10 mm		55	25	16	30SFTF10SXN
	13 mm		55	25	16	30SFTF13SXN

⚠ Please consider our security advices on the pages 12/13 ⚠

Tel: +45 63 12 83 00 | Email: ps@hymatik.com | www.hymatik.com | Hvidkaervej 27a, DK-5250 Odense SV, Denmark